

GRIPPS®

ANSI/ISEA
121-2018
COMPLIANT

H01006-5 / H01006-10 TOOL CATCH - 25MM X 90MM

The GRIPPS® Tool Catch offers a sturdy, dependable, and long-lasting retrofit tool connection solution for a wide range of hand tools.

Secure the GRIPPS® Tool Catch onto your tool using GRIPPS® V-Gripp Tape to establish a certified, load-rated tool connection point capable of withstanding rigorous industrial environments.

Sold in 5-packs and 10-packs.



2.5 KG **5.5** LB

MAX LOAD



ENGINEERED FOR DROP PREVENTION

GRIPPS.COM

KEY FEATURES



Robust Nylon for maximum strength and durability.

Easy installation process that can be done onsite.

Fully certified and load-rated when used with GRIPPS® V-Gripp Tape.

Closed and welded D-ring to prevent warping with use.

* Available in two sizes and in non-conductive.

SPECIFICATIONS

SKU	MAX LOAD	SIZES
H01005-5	1KG 2.2LB	12MM X 55MM 0.4IN X 2.1IN
H01005-10	1KG 2.2LB	12MM X 55MM 0.4IN X 2.1IN
H01006-5	2.5KG 5.5LB	25MM X 90MM 0.9IN X 3.5IN
H01006-10	2.5KG 5.5LB	25MM X 90MM 0.9IN X 3.5IN

HOW TO USE

1

Place Tool Catch with metal D-ring facing away from the tool's center of gravity with the white tag facing up.

2

Wrap the GRIPPS® V-Gripp Tape around the tool 10 x while stretching the tape to activate the self-vulcanising feature, creating a secure connection. Ensure the raised catch is not covered by the tape. Pull on the Tool Catch with force to test application.

3

Your Tool Catch is now ready to be connected with a suitable GRIPPS® tool tether using the D-ring.