

Cresto, Fusion Pro Single-flex 1601

Fall arrest Lanyard 1601

- CE and ANSI certified
- Approved for 140 Kg
- Elastic webbing

EN 355 : 2002



Product description

A single fall arrest lanyard provides secure protection when working on skylifts and scaffolding. Fusion Single-Flex S is manufactured as a flexible tube with internal elasticity, which allows you to stretch the line to a maximum length of 1.8 meters. At the beginning of the rope there is an external absorber mounted which is released in case of a fall. Unlike Fusion Twin-Flex S this fall arrest lanyard is ANSI certified and are approved for a user weight up to 140 kg. Between the absorber and the lanyard there is an aluminum ring to increase flexibility in use

Product properties

Brand	Cresto
Attaching connector 1	ANSI certified triple lock carabiner in aluminum
Attaching connector 2	Big ANSI certified aluminum hook with 64 mm opening
Minimum breaking strength - MBS (kN)	22
Energy absorber	Yes
Fall indicator	Yes
Maximum load (kg)	140
Maximum number of users	1
Mechanics	Tear-webbing absorber
Maximum working temperature (c)	100
Minimum working temperature (c)	-40
PPE-category	Category 3
Declaration of Conformity	Yes

EN-standard	EN 355 : 2002
Warranty	2+1 year when registered in Inspector
Identification	Serial number
Annual inspection	Yes, every 12 months
Life span	10 + 2 years. Product lifecycle 10 years + 2 years stock keeping
Notified body	1019, VVUU, a.S., Pikartska 1337/7 716 07 Ostrava - Radvanice Czech Republic
Other standards	ANSI Z359.13
RFID	Yes

Article information

Article number	Article name	Colors	L(cm)	Net weight (kg)
012203845	Cresto, Fusion Pro Singel-Flex	Black	1.8	2.09

Article number	Article name	GTIN	Tariff number	UNSPSC Code	Country of origin
012203845	Cresto, Fusion Pro Singel-Flex	7350015799981	56090000	46182302	Slovakia

Article number	Article name	Packaging type	W(cm)	H(cm)	L(cm)	Gross weight (kg)	Pieces / Pack
012203845	Cresto, Fusion Pro Singel-Flex	Carton	0	0	0	2.1	1